



Strip Till
STRIGER 100

PRODUCT INFORMATION



Invest in the row with STRIGER 100. Get exceptional output quality from this strip till tool with its easy settings that allow quick adaptation to all of your operations.



Comfort and precision

- Tool-free adjustment of trash removers
- Tool-free tine adjustment
- Hydraulic adjustment of tamping wheel

Perfect ground following

- Trapezium-mounted
- Gauge wheel in optimum position for cutting residues

New tine

- Quick-change point
- Lower pull-power requirement
- Fully protected leg



Highly adaptable

- Manure, liquid or solid fertilisers
- Different inter-row widths
- Two types of deflector disc
- Two types of opening disc
- Discs for springtime operations

High quality finish

Wire wheel : for fine soil
Chain wheel : for better water infiltration
Rubber wheel : for moisture retention

Safety in stony ground

- NSH tine safety up to 1,000kg
- Opening discs, trash removers and side deflectors with NSM safety system

Technical specifications

STRIGER 100

Models	300			440 R			600 R			
Chassis (m)	3,00			4,40			6,00			
Number of rows	4	5	6	6	7	8	8	9	11	12
Spacing (cm)	60 - 70 - 75 - 80	55 - 80	45 - 50	70 - 75 - 80	55 - 60	45 - 50	70 - 75 - 80	55 - 60	55	45 - 50
Transport width (m)	3,00									
Power requirement	Between 20hp and 35hp per row									
Working depth (cm)	From 7 to 30cm									
Linkage	Cat 2 - 3			Cat 3 - 4N - Quick Hitch 4N						
Necessary tractor hydraulic equipment	NSH and tamping wheel : 1 DA Trapezium : 1 DA			NSH and tamping wheel : 1 DA Trapezium : 1 DA						

KUHN HUARD.S.A.S. - 2, rue du Québec - Zone Horizon - FRANCE - 44110 Châteaubriant

Information given in this document is only for information purposes and is non-contractual. Our machines are in compliance with regulations in force in the country of delivery. In our literature, and for improved illustration of certain details, some safety devices may not be in operating position. When operating these machines, these devices must be in position in accordance with the requirements indicated in the operator's manuals and assembly manuals. Respect the tractor gross vehicle weight rating, its lift capacity and maximum load per axle and tyres. The tractor front axle load must always comply with the regulations of the country of delivery (In Europe, it must reach minimum 20% of the tractor net weight). We reserve the right to change any designs, specifications or materials listed without further notice. Machines and equipment in this document can be covered by at least one patent and/or registered design. Trademarks cited in this document may be registered in one or several countries.

To protect the environment, this leaflet is printed on chlorine-free paper. Printed in France - 950 058 EN - 09.21 - Copyright KUHN 2023

